

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 January 2005 (13.01.2005)

PCT

(10) International Publication Number
WO 2005/002735 A2

(51) International Patent Classification⁷: **B05B**

(21) International Application Number:
PCT/EP2004/051316

(22) International Filing Date: 30 June 2004 (30.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0315247.7 30 June 2003 (30.06.2003) GB

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and
(72) Inventor: REDDING, John [GB/GB]; Fleche Cottage,
Old Town Hill, Lamberhurst Kent TN3 8EN (GB).

(74) Agent: Brookes Batchellor LLP; 102-108 Clerkenwell
Road, LONDON Greater London EC1M 5SA (GB).


Published:

— without international search report and to be republished upon receipt of that report

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: IMPROVEMENTS IN OR RELATING TO SWIRLING FLUID FLOWS AND JETS



(57) Abstract: The present invention relates to improvements in or relating to swirling fluid flows and jets. In particular it concerns apparatus for controlled expansion (or contraction) of a swirling fluid flow, and a means for creating an annular swirling fluid flow, which, it will be shown, is particularly amenable to expansion. In one aspect, we describe a swirling fluid flow expansion apparatus comprising a flared nozzle having an inlet for operative connection to a swirling fluid flow, an outlet and an intermediate body having predetermined dimensional characteristics. We also describe embodiments of swirling fluid flow generators. In one embodiment, there is an inlet duct for operative connection to a pressurised fluid source, an outlet duct coaxial with the inlet duct and an intermediate generator body comprising at least one aperture defining a fluid flow path between the inlet duct and outlet duct wherein the fluid flow path has an axis orthogonal to that of the outlet duct. In another aspect, the generator comprises an impeller mounted within a duct having an inlet and an outlet defining a fluid flow path. The impeller includes an impeller

body having a central axial longitudinal flow blocking portion and star-shaped arms; the impeller further comprising impeller blades connected to, or formed with the impeller body, along a tangential line. We also describe a swirling fluid flow apparatus comprising a swirling fluid flow generator and a swirling fluid flow expansion apparatus as described above.